



applause 4-leg

arm, armless and tablet chairs in 4-leg and nesting frames

DESIGN

by Gino Gamberini

STANDARDS

Meets or exceeds ANSI/BIFMA X5.1 durability and safety standards.

CONSTRUCTION

THERMOPLASTIC SEAT & BACK: Textured thermoplastic

UPHOLSTERED SEAT & BACK: 3/4" polyfoam cushion on seat and 1/2" on back over 3/16" thick plywood

FRAME: 4-Leg: 25 mm cold rolled steel tube. 4-Leg Caster: 1" cold rolled steel tube. Seat and back connected with cast aluminum upright.

ARMS: Injection molded reinforced nylon with textured exposed surfaces. Available in Black only.

GLIDES: Non-abrasive reinforced nylon glides. Black only.

CASTERS: 50 mm dual wheeled soft floor hooded.

TABLETS: 5/8" diameter solid steel rod frame. Three-ply construction with high-pressure laminate top surface, 5/8" thick high-density particle board core, with moisture-resistant backing and 3/4" bumper T-edge molding. Tablet surface available in seven colors with coordinating edge.

STACKING


THERMOPLASTIC: 10 floor/10 dolly (10 floor/10 dolly w/ arm) (0 w/ tablet)

UPHOLSTERED PADS: 10 floor/ 10 dolly (10 floor/ 10 dolly w/ arm) (0 w/ tablet)

4-WHEEL DOLLY

00069 (\$279)

OW 24.5" OD 21" OH 7.5" WT 20 lb



CONSTRUCTION: steel; two swivel casters and two fixed casters; black epoxy

see page 61 for dolly section