



## bola

arm and armless chairs in fixed and flexing back; fixed back tablet chairs also available

### DESIGN

by Ron Kemnitzer

### STANDARDS

Meets or exceeds ANSI/BIFMA X5.1 durability and safety standards. Bola® chairs can pass CAL 133 fire standards with "CF" or "CA" option.

### CONSTRUCTION

**THERMOPLASTIC SEAT & BACK:** Textured thermoplastic.

**UPHOLSTERED SEAT & BACK:** Seat: Upholstered 2" urethane foam over contoured molded plywood. Back: Upholstered 1" urethane foam over contoured molded plywood. 1/4" urethane foam on back cover.

**FRAME:** 1" x 16 gauge steel tube.

**ARMS:** Epoxy finish to match frame with molded plastic inserts. Arm inserts will match seat and back color for thermoplastic models. Chairs specified with bright chrome will have gunmetal arms with specified inserts.

**GLIDES:** Molded nylon ball or formal glides.

**END CAPS:** Molded nylon; color will coordinate with frame finish

**FLEX BACK POST:** Spring Steel; finish will coordinate with frame

**TABLETS:** 1" diameter, 12 gauge tubular steel frame. Three-ply construction with high-pressure laminate top surface, 5/8" thick high-density particle board core with moisture-resistant backing and 3/4" bumper-T edge molding. Tablet surface available in seven colors with coordinating edge.

### STACKING

**THERMOPLASTIC:** 4 floor/4 dolly (4 floor/4 dolly w/ arm)

**UPHOLSTERED:** 4 floor/4 dolly (4 floor/4 dolly w/ arm) (4 floor/4 dolly w/ upholstered tablet)

### 2-WHEEL DOLLY

00003 (\$292)

OW 25" OD 10" OH 51" WT 30 lb

**CONSTRUCTION:** steel; ball bearing wheels; black epoxy




### 4-WHEEL DOLLY

00005 (\$273)

OW 26" OD 28" OH 5.5" WT 31 lb

**CONSTRUCTION:** steel; swivel casters; black epoxy



see page 61 for dolly section