



pulse

arm, armless and tablet chairs with flexing frame and lumbar support

DESIGN

by Peter Haas

STANDARDS

Meets or exceeds ANSI/BIFMA x 5.1 durability and safety standards.

CONSTRUCTION

THERMOPLASTIC SEAT & BACK: Textured thermoplastic

UPHOLSTERED SEAT & BACK PADS: Upholstered 1/2" urethane foam over contoured molded 3-ply plywood for seat and back. Lumbar has 1/2" urethane foam over contoured thermoplastic.

FRAME: 1/2" diameter solid steel rod.

ARMS: Injection molded polypropylene with textured surface. Arm caps will match seat and back finish

GLIDES: Optional snap-on clear plastic.

TABLETS: 5/8" diameter solid steel rod with 1/2" diameter solid steel rod support. Three-ply construction with high-pressure laminate top surface, 5/8" thick high-density particle board core, with moisture-resistant backing and 3/4" bumper T-edge molding. Tablet surface available in seven colors with coordinating edge.

STACKING


THERMOPLASTIC: 6 floor/10 dolly (6 floor/10 dolly w/ arm) (0 w/ tablet)

UPHOLSTERED: 6 floor/10 dolly (6 floor/10 dolly w/ arm) (0 w/ tablet)

4-WHEEL DOLLY

00059 (\$295)

OW 26.5" OD 37" OH 26" WT 45 lb



CONSTRUCTION: steel; two swivel casters and two fixed casters; black epoxy

see page 61 for dolly section